

**WHAT IS CLAIMED:**

1. An optical cross-connect device, comprising:

at least one shelf having a plurality of guide rails  
5 running in parallel thereon;

a switch motherboard disposed at the rear end of said  
shelf;

at least one electric crosspoint switch disposed on the  
outer surface of said switch motherboard;

10 a plurality of switch connectors positioned on the front  
surface of said switch motherboard; and,

a plurality of optical transceiver boards mounted along  
said guide rails of said shelf, said optical transceiver  
having a transceiver connector for connecting to a different  
15 one of said switch connectors positioned on the front surface  
of said switch motherboard.

2. The device according to claim 1, wherein said  
electric crosspoint switch is disposed at the front center  
20 portion of said switch motherboard, and wherein a multiple  
array of said switch connectors are disposed near said  
electric crosspoint switch.

3. The device according to claim 1, wherein said electric crosspoint switch and said switch connectors are connected through an impedance signal line that is formed on said switch motherboard.

5

4. The device according to claim 1, wherein said guide rails enable said optical transceiver boards to be vertically mounted on said shelf.

10

5. The device according to claim 1, wherein said guide rails maintain a predetermined interval distance between said optical transceiver boards.

15

6. The device according to claim 1, wherein each of said optical transceiver boards is slidably mounted along said guide rail of said shelf to enable said optical transceiver board to be electrically coupled to one of the plurality of said switch connectors.

20

7. An optical cross-connect device, comprising:

at least one shelf having a plurality of guide rails running in parallel thereon;

a switch motherboard disposed at the rear end of said shelf;

at least one electric crosspoint switch disposed on the outer surface of said switch motherboard;

at least one array of switch connectors disposed on the outer surface of said switch motherboard; and,

a plurality of optical transceiver boards slidably mounted along said guide rails of said shelf to enable said optical transceiver board to be electrically coupled to one of the plurality of said switch connectors.

8. The device according to claim 7, wherein said electric crosspoint switch is disposed at the front center portion of said switch motherboard.

9. The device according to claim 7, wherein said electric crosspoint switch and said switch connectors are connected through an impedance signal line that is formed on said switch motherboard.

10. The device according to claim 7, wherein said guide rails enable said optical transceiver boards to be vertically mounted on said shelf.

5 11. The device according to claim 7, wherein said guide rails maintain a predetermined interval distance between said optical transceiver boards.

10 12. The device according to claim 7, wherein each of said optical transceiver boards is slidably mounted along said guide rail of said shelf to enable said optical transceiver board to be electrically coupled to one of the plurality of said switch connectors.